



MANGUERAS POLIAMIDAS	
USO:	INDUSTRIAL
UTILIZACION:	AIRE
CARACTERISTICAS	EXPELENTE
TIPO: POLIAMIDAS NATURAL, POLIAMIDA MILIMETRICA, TUBOS ESPIRALADOS (AZUL, ROJO, NEGRO, NATURAL)	

POLIAMIDA NATURAL		
CODIGO	DIAM. INT. M.M.	PRESION DE TRABAJO (KG/CM2)
204-2	1/8 ESP. 0.40	125
204-3	3/16 ESP 0.60	85
204-4	1/4 ESP 0.80	76
204-5	5/16 ESP 1.00	78
204-6	3/8 ESP 1.20	64
204-8	1/2 ESP 1.60	82
204-12	3/4 ESP 2.00	68
204-12-25	3/4 ESP 2.50	68



POLIAMIDA MILIMETRICA		
CODIGO	DIAM. INT. M.M.	PRESION DE TRABAJO (KG/CM2)
204M-4-1	4MM X 1	160
204M-6-2	6MM X 2	120
204M-8-2	8MM X 2	73
204M-10-2	10MM X 2	68
204M-11-15	11MM X 1.5	70
204M-12-1	12MM X 1	80
204M-12-15	12MM X 1.5	50



TUBOS ESPIRALADOS	
CODIGO	DIAM. INT. M.M.
RE-4-2500	1/4 X 2500
RE-4-5000	1/4 X 5000
RE-4-7500	1/4 X 7500
RE-4-12000	1/4 X 12000
RE-5-2500	5/16 X 2500
RE-5-5000	5/16 X 5000
RE-5-7500	5/16 X 7500
RE-5-12000	5/16 X 12000
RE-6-2500	3/8 X 2500
RE-6-5000	3/8 X 5000
RE-6-7500	3/8 X 7500
RE-6-12000	3/8 X 12000
RE-8-2500	1/2 X 2500
RE-8-5000	1/2 X 5000
RE-8-7500	1/2 X 7500
RE-8-12000	1/2 X 12000

