



TECALAN NEGRO	
USO:	INDUSTRIAL
UTILIZACION:	AIRE COMPRIMIDO
CARACTERISTICAS	EXPELENTE-ASPIRANTE
TIPO: TECALAN (NEGRO)	

TECALAN NEGRO		
CODIGO	DIAM. INT. M.M.	PRESION DE TRABAJO (KG/CM2)
204T-4-2	4 X 2	130
204T-6-4	6 X 4	90
204T-8-6	8 X 6	60
204T-10-8	10 X 8	50
204T-11-8	11 X 8	65
204T-12-9	12 X 9	60
204P-1-4	1/4	87
204P-5-16	5/16	48
204P-3-8	3/8	48
204P-1-2	1/2	38



TEFLON C/MALLA Y REMALLADA	
USO:	INDUSTRIAL
UTILIZACION:	LIQUIDOS NO CORROSIVOS
CARACTERISTICAS	EXPELENTE-ASPIRANTE
TIPO: TEFLON C/MALLA (BLANCA), REMALLADA (NEGRA)	

TEFLON C/MALLA		
CODIGO	DIAM. INT. M.M.	
212-3	3/16	
212-4	1/4	
212-5	5/16	
212-6	3/8	
212-8	1/2	
212-10	5/8	
212-12	3/4	
212-16	1"	



MANGUERA REMALLADA		
CODIGO	DIAM. INT. M.M.	
205-3	3/16	
205-4	1/4	
205-5	5/16	
205-6	3/8	
205-8	1/2	
205-9	9/16	
205-10	5/8	
205-12	3/4	
205-16	1"	

